



#### SPECIFICATIONS

**Suitable for :** Inside/Outside

**Type :** Ankle shoe

**Activity :** Construction / Storage, Logistic, Transport / Electronic Industry, ESD

**Upper :** Water resistant full supple leather and CORDURA® material

**Lining :** ARTICO® black color, up to the toes, slipper feeling

**Tongue :** Bellows tongue in ON STEAM® microfibre, lining ARTICO® and padded with 10mm thick foam

**Ankle protection :** CORDURA® material, ARTICO® lining and padded with 10mm thick foam

**Fastening :** Round polyester black laces with «Quick lock» system

**Toe cap :** Ultralight and extra wide 200 joules, Composite LIGHT SYSTEM®

**Midsole :** Composite FLEX SYSTEM®, anti-magnetic and thermal insulated

**Insole :** Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH®

**Sole :** PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-CI

**Sole pattern :** Multi-purpose cleated indoor/outdoor outsole, well-defined heel, cleated arch, SRC standard

**Weight (Kg/pair) :** 1.200

**Colors :** Black upper and dark grey/light grey outsole

**Sizes :** 35-48 (2-13)

**Standards :** EN ISO 20345:2011 SRC / EN 61340-5-1 / DGUV 112-191





**EC Certificate of Conformity N° :** 0075/020/161/08/17/1266 - EXT 08/09/17

**Special features :** Quick fastening system «Quick lock»

**Special features 2 :** Reflective piping on the heel part



#### SPECIFIC FEATURES










-  Integral 100% composite (Air System + Light System + Flex System)
-  Metal free, non magnetic
-  Water absorption and penetration resistance of upper (WRU)
-  Electro Static Discharge Standard EN 61340-5-1

**CORDURA**



Doublelayer **ARTICO**

#### GENERAL FEATURES

-  Antistatic properties (A)
-  Heel energy absorption (E)
-  Abrasion resistance
-  Crampon sole
-  Heat-insulated sole (HI)
-  Cold-insulated sole (CI)
-  200 joule extra-wide toecap
-  Hyper-ventilated lining
-  Perforation-resistance 1100 N (P)