



CONTIPHARMA

a member of Bedelco group

PROTECT

Hppe Guyard MecaSafe 6550 30 knitted



SPECIFICATIONS

- HPPE knitted glove / glass fiber, polyurethane coating.
 - Intermediate risks - Cat. II.
-

CHARACTERISTICS

- High density polyethylene knit 50.0%, fiberglass 25.0%, polyester 22.0%, spandex 3.0%.
 - Grey polyurethane coating in the palm.
 - Ventilated back.
 - Elasticated cuff with colored overlay indicating size.
 - Available sizes: 6 to 11.
-

CONFORMANCE

- Declaration issued by the CTC (France) n 00075 EN 420 1 03 + A1 / 09 - EN 388 12016 - EN ISO 13997.
 - EU declaration 2016/425 on request.
-

USES OF RECEIVED USES

- Handling of dry or slightly greasy cutting parts, glass.
- Industry, construction.



PERFORMANCE NEIGHBOURS

- Abrasion : 4 / 4
 - Cutting EN 388 / 2016 : 4 / 5
 - Tear : 4 / 4
 - Perforation : 3 / 4
 - Cutting EN ISO 13997 : D / F
-

PRECAUTIONS OF THE LAW

- Before reuse, check the gloves for defects, holes, tears or abnormal wear.
 - Wear gloves on dry and clean hands. Pre-testing of gloves is recommended as actual use conditions may differ from EU type testing.
-

PROTECTION LIMITES

- Do not use for handling objects with a temperature above 50°C.
 - Do not use for handling chemicals or liquids.
-

SAFETY, COMFORT & DEXTERITY

- Dexterity, level 5.
 - This PPE does not contain substances at levels known or suspected to have adverse effects on the hygiene or health of the user under the foreseeable conditions of use.
-

CONDITIONNEMENT

- Bag : 10 pairs.
 - Boxes: 200 pairs.
-

MAINTENANCE AND STORAGE

- No particular maintenance is recommended.
- It is recommended to store the products in a dark, cool, dry and ventilated place.
- The destruction at the end of life must be controlled and respect the European requirements of traceability and respect of the environment.